

Port of Arendal - Eydehavn Multi-Purpose Terminal

1. Terminal & Contact

| Item | Data |
|-------------|--|
| Terminal | Eydehavn Multi-Purpose Terminal 58.29,8 N – 08.52,7 E |
| UN LOCODE | NO EYD |
| VHF | Ch. 12 (Port Control), Ch. 16 |
| Address | Kristen Staksnæs vei 61, 4810 Eydehavn |
| Contact | +47 975 27 000 post@arendalhavn.no |
| PFSO / HM | +47 975 27 000 |
| ISPS status | Certified. Secured port facility (access via gate, ID checks). Normal level 1. |

2. Pilotage & Approach

| Item | Data |
|----------------|--|
| Pilotage | Mandatory ≥ 70 m LOA (or ≥ 50 m pax) |
| Booking | SafeSeaNet ≥ 24 h prior |
| Pilot stations | 58.39154 N 8.81006 E outside Ytre Torungen lh. Alternative boarding outside Bonden lh eastern approach upon request. |
| Approach | Eastern approached through Tromøysund, easily navigated waters, min. depth: 17 m, no height restrictions |
| Alternative | Via Galtesund, easily navigated waters, min depth: ~ 8.5 m, max air draft: 34 m |
| Anchorage | By request to Arendal Port Authority |

3. Fairway & Basin

| Item | Data |
|----------------|---------------------------------|
| Depths | Min: 17 m in approach |
| Tidal range | ± 0.2 m (insignificant) |
| Ice conditions | Ice-free |
| Turning area | 400 m (Buøya) / 500 m (Saltrød) |
| Currents | Typically, ≤ 0.5 kn |

4. Berths

| Berth | Length | Max draft | Max LOA | Notes |
|-----------------|--------|-----------|---------|--------------------------|
| Main Quay | 370 m | 11.0 m | 220 m | Height: 2.40m |
| RoRo ramp width | 30 m | 11.0 m | 220 m | Fixed ramp/slope: 6 deg. |

5. Mooring & Equipment

| Item | Data |
|-------------|--|
| Bollards | SWL 70 ton |
| Fenders | Rubber panel/cell |
| Linesmen | On request |
| Tug options | LOA 130 m. One tug 30 TBP. LOA > 150 m two tugs / one with 50 TBP. Captain can apply for exception/reduction to pilot master base on ship particulars. |

6. Cargo Handling Equipment

| Equipment | Qty | Capacity |
|-------------------|-----|-------------|
| Liebherr LHM 550 | 1 | 144 t |
| Gottwald HMK 260E | 1 | 104 t |
| Reachstackers | 2 | 45 t |
| Heavy forklift | 1 | 14 t |
| Light forklifts | 1–2 | 2.5 t |
| Terminal tractor | 1 | 32 t |
| Reefer outlets | 20+ | 440 V |
| Container depot | – | 300–500 TEU |

7. Services Alongside

| Service | Data |
|---------------|------------------------------------|
| Fresh water | 20–50 m ³ /h |
| Shore power | 690 V / 400 V / 700 A / 50 & 60 Hz |
| Reefer power | 440 V outlets |
| Bunkering | On request |
| Waste | On request |
| Sludge/sewage | On request |
| Crew change | Kjevik Airport 77 km |



Arendal Havn

PORT INFO SHEET

8. ISPS & Safety

| Item | Data |
|----------|-----------|
| ISPS | Yes |
| Access | ID/escort |
| PPE | Mandatory |
| Hospital | 20 min |